



## Technical Data

### Colour Variation

Slight variations in colour may occur between production runs.

### Transmitted Light and Colour

Transmitted light and colour may vary in intensity depending on weather conditions. It should be noted that the sheet colour will determine the colour of the transmitted light. This should be viewed prior to purchase to avoid disappointment.

### Condensation

Under single skin roofs of any sort, and especially in cold temperatures, condensation is generally unavoidable. Good ventilation will always help minimise condensation.

## Do's and Don'ts

### Do's

- ✓ Allow adequate ventilation to prevent heat build-up.
- ✓ Clean with warm soapy water and a soft sponge. Hose down thoroughly.
- ✓ Install corrugated profile at a minimum pitch of 5° (88mm rise per lineal metre) and Deka at a minimum pitch of 2°.
- ✓ Pre-drill fixing holes to allow for expansion and contraction. Use a 10mm drill.
- ✓ Read the installation instructions before commencing installation.
- ✓ Store sheets on a flat surface.
- ✓ Use Laserlite Noise Stop Tape on top of purlins to minimise the noise associated with expansion and contraction.
- ✓ Use only Laserlite brand fixings and weatherseals as any failure resulting from fixings other than Laserlite brand fixings will not be covered by warranty.

### Don'ts

- ✗ Allow moisture to get between sheets in storage as this may cause whitening.
- ✗ Store in direct sunlight.
- ✗ Walk directly on sheeting.

## Handling and Storage

The following points will assist with preventing damage to your Fibreglass sheets during storage and handling:

- Store sheets on a flat surface
- Store out of direct sunlight
- Don't allow moisture to get between the sheets while in storage
- Do not walk directly on the sheeting.

